INKER & RASOR

Portable Reference Electrodes Copper-Copper/Sulfate

Models: 2-A Pencil cell 3-A for concrete 6-A, 8-A Flat Tips 6-B, 8-B Pointed Tips

Features:

Long lasting tips Strong body for outdoor use High purity copper High purity copper-sulfate Optional Clear View tube Temperature sensor



AVAILABLE FROM STOCK! Distributed by

www.tinker-rasor.com

www.teststations.com

Info@tinker-rasor.com

www.detectron.com



Tinker & Rasor quality is found in our products, our people and our customer service.





MODELS 2-A, 3-A, 6-A, 6-B, 8-A and 8-B

Features:

- · Flat or Pointed Tips
- · Tip grooves provide greater surface area
- · Tips pre-saturated with copper-sulfate
- Knurled nut on 1/4" 20 (except 2-A) threaded rod for easy lead connection (fork, ring, etc)
- Model 2-A, #6 knurled nut on 10-32 threaded copper rod.
- Charged with copper-sulfate
- Multiple Diameters and Lengths available

Construction:

- New, tougher body
- Optional Clear View Tube
- Stronger, longer lasting tips
- O-ring seals

Applications:

- Pipe to Soil potentials
- Close Interval Surveys
- Structure to Cell
- Lab use

Recommendations:

Use with most CP Voltmeters Half cell models 3, 6 & 8 screw into back of T&R CPV-2 and CPV-4 CP Voltmeters

Specifications:

High purity copper rod High purity copper-sulfate crystals

Dimensions:

2-A: 3/8" x 5-3/4" 3-A: 3" x 5" 6-A: 1-1/4" x 6" 6-B: 1-1/4" x 7" 8-A: 1-1/4" x 8" 8-B: 1-1/4" x 9"

DELIVERY: Immediately from STOCK F.O.B. San Bernardino, CA USA SERVICE: 24-hour Turn-Around TERMS: Net30 Days, on approval of credit WARRANTY: 90 Days, parts and labor _____



AVAILABLE FROM STOCK